

CSS Variable Wizardry

— STUDY GUIDE —





What Are CSS Variables?

Custom properties that store specific values for reuse throughout a stylesheet. Think of them as named 'runes' or **labels for values**, not mini CSS files. They turn your stylesheets into a living control panel.

```
/* Declaration in :root */  
:root {  
  --rune-text-strong: #ffffff;  
}
```

Why They Matter



Declaring Global Runes in `:root`

Define variables in the `:root` selector to create global tokens accessible to your entire application. This is the central source of truth for your design system.


```
:root {  
  --page-bg: #0f172a;  
  --arcane-accent: #f97316;  
  --glyph-border: #fde68a;  
  --rune-text-strong: #ffffff;  
  --potion-liquid: #f97316;  
  --potion-glow: 0 0 32px rgba(249, 115, 22, 0.65);  
}
```

Using Variables with `var()`

The `var()` function retrieves the value of a custom property. It's the incantation used to summon a rune's power. It literally means: "grab the computed value of this variable from its cascade."

```
/* In :root */  
--potion-liquid: #f97316;
```

```
/* In a component */  
.potion-beaker {  
  background-color: var(--potion-liquid);  
}
```



Scope & The Cascade

Variables don't dodge the cascade—they **use** it. Values are inherited from parent elements unless a more specific (local) value is defined.

Hierarchy of Power

- * **1. ``root`` (Global):** The base design tokens for the entire document.
- * **2. **Component/Section** (Local):** Overrides global values for a specific context, like a ``dark-theme`` wrapper.
- * **3. **Element** (Most Specific):** The final override, closest to the point of use. **The deepest spell wins.**

Building a Color System

Use variables to define a clear, consistent, and maintainable color palette. Changing a rune once can shift the entire lab's mood.



Local Overrides

Override a global variable inside a specific selector to change its value only within that scope.
Perfect for creating component variants without writing new properties.

Global Value (Inherited)



Beaker uses the default ``-potion-liquid: #22d3ee;`` from its parent lab.


Local Override (Scoped)



```
/* Bottom-shelf variant: override only the liquid */  
.potion-card--lower-override {  
  --potion-liquid: #ec4899; /* neon pink */  
}
```

Theme Switching with JavaScript

Hand the wand to JavaScript to rewrite variable values at runtime.
JavaScript only updates the tokens; CSS and the cascade handle the rest.



```
// JS defines theme values
const THEMES = {
  sun: { liquid: '#f97316', glow: '...' },
  violet: { liquid: '#ec4899', glow: '...' }
};

// And sets them on the root element
function applyTheme(key) {
  const theme = THEMES[key];
  document.documentElement.style.setProperty(
    '--potion-liquid', theme.liquid
  );
}
```

Variables + Functions

Combine variables with CSS functions to create dynamic and responsive values.
Use them as unitless 'intensity knobs' for motion, shadows, and spacing.

`calc()`

`clamp()`

`min()`

```
:root {  
  --lift-distance: 14px; /* The intensity dial */  
}  
  
.card:hover {  
  /* The spell */  
  transform: translateY(calc(-1 * var(--lift-distance)));  
}
```

Before vs. After Refactor

Refactoring to variables makes your CSS cleaner, more readable, and infinitely more maintainable. You stop hardcoding colors like it's 2009 and start wielding design tokens.

Before: Hard-Coded Values

```
.button-primary {  
  background: #ec4899;  
}  
  
.modal-header {  
  border-bottom: 2px solid #ec4899;  
}  
  
.link:hover {  
  color: #ec4899;  
}
```



After: Variable-Driven

```
:root {  
  --brand-accent: #ec4899;  
}  
  
.button-primary {  
  background: var(--brand-accent);  
}  
  
.modal-header {  
  border-bottom: 2px solid  
    var(--brand-accent);  
}  
  
.link:hover {  
  color: var(--brand-accent);  
}
```

Common Mistakes to Avoid



Forgetting Fallbacks

Not providing a fallback value in `var()` can break styles if a variable is missing.

```
color: var(--missing-var, black);
```



Unclear Naming

Vague names like `--c1` or `--main-red` create confusion. Use semantic names like `--color-brand-accent` or `--color-status-danger`.



Storing Properties, Not Values

A variable stores only the value part, not an entire declaration.

```
Incorrect: --fancy-border: border: 3px solid hotpink;  
Correct: --fancy-border-color: hotpink;
```

Best Practices for Potent Magic



Consistent Naming Conventions: Use a clear system, such as `[category]-[property]-[variant]`.

**Example*:* `--color-brand-primary`, `--font-size-heading-lg`



Global Palette, Local Consumption: Define foundational brand tokens in `:root`. Components should consume these tokens, not redefine them.



Component Defaults: Give components safe, self-contained default values. This allows them to look correct even out of context, while parents can still override them.

**Example*:*

```
.card { --card-bg: #0f172a;
background: var(--card-bg); }
```

Master the magic. Wield the variables.

"Should this be a rune? If you use it more than once, the answer is: *yes, apprentice.**"

p.s., keep learning!

